



Standard Vertical Compressor

Made in the "USA"

Hypres Equipments' standard vertical compressors are comprised with a North American pump. The pump is capable of 9 to 18 CFM. Three and four stage designs for low vibration. Pressures rated at 5000 to 6000 psi. The pumps have a 56 decibel rating for quiet operation. Heavy duty crank shafts, gear type oil pump, & spin on oil filter provide longer pump life. The standard system is equipped with a magnetic starter and overload protector with 24 VAC Siemens controller.

Standard Equipment:

- Stainless Steel Gauge Panel
 - Hour meter
 - Oil pressure gauge
 - Gauges for each stage
 - High temperature light
 - Low oil pressure indicator light
 - On/Off switch
 - Power indicator light
- Single phase or three phase electric
- Replaceable cartridge type purification system providing up to approx. 60,000 SCF of Grade 'E' air between cartridge changes
- See view indicator visually monitoring moisture and CO elements in the air supply
- Automatic condensation drain system eliminating condensate buildup every 15 mins.
- High pressure shutdown & auto on switch
- High temperature shutdown switch
- Relief valves on each stage of compression
- Intercoolers/Aftercoolers
- Six foot fill hose with SS CGA hand tight adapter and bleed valve



Dimensions: 38.5"W x 30"D x 62" H

Options:

- CO monitor
- Moisture monitor

Hypres Equipment

7608 Melrose Lane Oklahoma City, OK 73127

405-440-2442 • Fax 405-440-2471

www.hypresequip.com • sales@hypresequip.com